

Commercial Lighting Designs  
 Website: www.commerciallightingdesigns.com.au  
 Email: info@commerciallightingdesigns.com.au  
 Phone: 02 8014 3897  
 Address: 1/13 Watson Road Padstow 2213



# Vector Gimble Downlight

## Rectangular Shop Light

- Easily adjustable beam direction.



60 adjustable degree

### FEATURES

- Die-cast aluminium heat sink
- High efficiency SMD chips
- Constant current driver
- 60 degree gimble angle

### INCLUDES

- Gimble LED downlight
- Non-dimmable driver
- 1.2 m flex and plug

### APPLICATIONS

- Residential and hotels
- Conference rooms and reception areas
- Retail and commercial
- Aged care

### WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)
		Non dim	Ra≥80		

Part No.	Voltage	Watt.	PF	CCT.	Lumen	Beam Angle	Lifetime L70B50	Cutout (mm)	Net Weight (kg)
173113	220-240V	38W	0.9	3000K	3800lm	100°	50000h	227x130	1.50
173114	220-240V	38W	0.9	4000K	4100lm	100°	50000h	227x130	1.50

Part No.	Model No.	VEET Status	IPART Status
173113	YKRSR01-38W	Approved No.: 5638	Approved No: 24143D15-KFHFFAFE
173114	YKRSR01-38W	Approved No.: 5638	Approved No: 24143D15-KFHFFAFE

[1] Operating Frequency=50/60Hz;

[2] Operating Temperature:-20 °C~+40 °C

