



Vector Round Downlight

Larger Diameter Dimmable Downlight

- Ideal for replacement of existing 6 inch and 8 inch luminaires.



FEATURES

- Die-cast aluminium heat sink
- High efficiency SMD chips
- Constant current driver
- Opal polycarbonate diffuser
- IP54 weatherproof
- 160mm and 195mm cutout size

DIMMING OPTIONS

- Trailing and Leading Edge
- Universal

INCLUDES

- Fixed head LED downlight
- Dimmable LED driver
- 1.2 m flex and plug

APPLICATIONS

- Residential and hotels
- Conference rooms and reception areas
- Bathrooms and wet areas
- Retail and commercial
- Aged care

WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION		IP RATING	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)
			 leading and trailing edge	 Ra≥80	 35W	 25W 35W

Part No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Cutout (mm)	Fitting Colour	Net Weight (kg)
2039	220-240V	25W	0.9	3000K	2000lm	90°	50000h	160	White	0.97
2040	220-240V	25W	0.9	4000K	2200lm	90°	50000h	160	White	0.97
2047	220-240V	35W	0.9	3000K	3000lm	90°	50000h	195	White	1.30
2048	220-240V	35W	0.9	4000K	3300lm	90°	50000h	195	White	1.30

Part No.	Model No.	Driver Model No.	VEET Status	IPART Status
2039 2040	YKRS6E1-D WT	YKD25CC470D	Approved No.: 4319	Approved No.: 24143S15-MAIH8IF
2047 2048	YKRS8E1-D WT	YKD35CC700D	Approved No.: 4319	Approved No.: 24143S15-MAIH8IF

[1] Operating Frequency=50/60Hz;

[2] Operating Temperature:-20C~+40C

