



Stellar Tri-color LED Batten

Multi-purpose Modular Batten

- Tri-colour, dual power batten.



FEATURES

- Built-in high efficiency SMD chips
- Highly transparent opal polycarbonate diffuser
- CCT selectable via DIP switch
- Dual power design
- Large 6mm terminal block for easy installation
- Quick install modular design
- Microwave sensor option available.
Made to order and MOQ applies.
- Fitting colour: White

INCLUDES

- Dual wattage / light output switchable driver
- Mounting accessories

INSTALLATION OPTIONS

- Surface mounted
- Suspended(suspension kit is required)

APPLICATIONS

- Offices
- Garages
- Stations
- Industrial

WARRANTY

- Five years (subject to terms and conditions)

Battens

CERTIFICATION	IP RATING	DIMMABLE	TRI-COLOUR	Ra	DISTRIBUTION	DIMENSIONS(mm)

Part No.	Voltage	Watt.	PF	CCT.	Lumen	Beam Angle	Lifetime L70B50	Size (L*W*H)mm	Net Weight (kg)
211000	220-240V	10/21W	0.9	4000K/5000K/6500K	900/1850lm	120°	50000h	600*80*65	1.00
211001	220-240V	21/42W	0.9	4000K/5000K/6500K	1850/3800lm	120°	50000h	1200*80*65	1.90

Part No.	Model No.	VEET Status	IPART Status
211000	YKT8BG2-TC-L60 21W	Pending	Pending
211001	YKT8BG2-TC-L120 42W	Approved No.: 5684	Approved No.: 24143S20-FGEEHG

[1] Operating Frequency=50/60Hz;

[2] Operating Temperature:-20 °C~+50 °C

