

Commercial Lighting Designs

TEL:02-80143897 Fax:02-87640606 Email:info@commerciallightingdesigns.com.au



CONSERVER

For a lighter, brighter future


SPEC SHEET: LED T8 Batten 600mm and 1200mm

CONSTRUCTION

- Pressed steel base with PVC body
- Powder coated finish
- High efficiency LED T8 tubes fitted
- Opal PMMA diffuser
- Large terminal block, easy installation
- Safety fuse installed



DIMENSIONS



TECHNICAL SPECIFICATION

Input	Power	Lumen	CCT	Beam Angle	CRI	Fitting Colour	Dimensions L x W x H
240V	9W	650lm	3000K	120°	>80	White	625 x 65 x 77 mm
240V	9W	700lm	4000K	120°	>80	White	625 x 65 x 77 mm
240V	9W	750lm	6000K	120°	>80	White	625 x 65 x 77 mm
240V	18W	1300lm	3000K	120°	>80	White	1225 x 65 x 77 mm
240V	18W	1400lm	4000K	120°	>80	White	1225 x 65 x 77 mm
240V	18W	1500lm	6000K	120°	>80	White	1225 x 65 x 77 mm
240V	2 x 9W	2 x 650lm	3000K	120°	>80	White	625 x 110 x 77 mm
240V	2 x 9W	2 x 700lm	4000K	120°	>80	White	625 x 110 x 77 mm
240V	2 x 9W	2 x 750lm	6000K	120°	>80	White	625 x 110 x 77 mm
240V	2 x 18W	2 x 1300lm	3000K	120°	>80	White	1225 x 110 x 77 mm
240V	2 x 18W	2 x 1400lm	4000K	120°	>80	White	1225 x 110 x 77 mm
240V	2 x 18W	2 x 1500lm	6000K	120°	>80	White	1225 x 110 x 77 mm