



# Tempest Nova Batten

## Weatherproof Batten With LED Tube

- Weatherproof batten with LED tubes.



### FEATURES

- High efficiency LED T8 tube fitted
- High impact body and diffuser
- Large 6mm terminal block for easy installation
- Safety fuse installed
- IP65 weatherproof and IK08 vandal-proof
- Fitting colour: Grey

### INCLUDES

- IP65 batten with LED tubes
- Stainless steel clips and screws
- Suspension bracket and cable gland

### INSTALLATION OPTIONS

- Surface mounted
- Suspended (Suspension kit is required)
- Side and top cable entry options

### APPLICATIONS

- Warehouses
- Car parks
- Stations
- Food preparation areas

### WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)	IK RATING
		Non dim	Ra≥80			IK08 1.7kg at 300mm

Part No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Size(L*W*H)mm	Net Weight (kg)
212009B	220-240V	1×9W	0.9	4000K	800lm	125°	40000h	662*89*90	0.90
212010B	220-240V	2×9W	0.9	4000K	1550lm	125°	40000h	662*130*90	1.12
212011B	220-240V	1×20W	0.9	4000K	1800lm	125°	40000h	1265*89*90	1.60
212012B	220-240V	2×20W	0.9	4000K	3500lm	125°	40000h	1265*130*90	2.00
212604B	220-240V	1×9W	0.9	6500K	800lm	125°	40000h	662*89*90	0.90
212605B	220-240V	2×9W	0.9	6500K	1550lm	125°	40000h	662*130*90	1.12
212606B	220-240V	1×20W	0.9	6500K	1800lm	125°	40000h	1265*89*90	1.60
212607B	220-240V	2×20W	0.9	6500K	3500lm	125°	40000h	1265*130*90	2.00

Part No.	Model No.	VEET Status	IPART Status
212009B 212604B	ECTPLC2-1L60 9W	Approved No.: 5428	Approved No.: 24143S20-U3RFB1
212010B 212605B	ECTPLC2-2L60 18W	Approved No.: 5428	Approved No.: 24143S20-U3RFB1
212011B 212606B	ECTPLC2-1L120 20W	Approved No.: 5428	Approved No.: 24143S20-U3RFB1
212012B 212607B	ECTPLC2-2L120 40W	Approved No.: 5428	Approved No.: 24143S20-U3RFB1

[1] Operating Frequency=50/60Hz;

[2] Operating Temperature:-20 °C~+45 °C

Specifications are for reference only and may be changed without prior notification.

