



- Integrated weatherproof batten with microwave dimming sensor.



FEATURES

- Weatherproof and vandal resistant
- Multi-power selection through DIP Switch
- Built-in motion & daylight microwave sensor
- High impact body and diffuser
- High efficiency SMD LED chips
- Vandal resistance level: IK08
- Stainless steel clips and screws
- Fitting colour: Grey

INCLUDES

- 0-10V dimmable driver
- Motion & daylight microwave sensor
- Mounting accessories
- Suspension bracket included

INSTALLATION OPTIONS

- Surface mounted
- Suspended (Suspension cable is required)

APPLICATIONS

- Warehouses
- Car parks
- Stations
- Food preparation areas

WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)	IK RATING
						 1.7kg at 300mm

Part No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Size(L*W*H)mm	Net Weight (kg)
213034DS	220-240V	20W	0.9	4000K	2000lm	120°	50000h	662*130*90	1.37
213035DS	220-240V	20W	0.9	5000K	2000lm	120°	50000h	662*130*90	1.37
213036DS	220-240V	20W	0.9	6500K	2000lm	120°	50000h	662*130*90	1.37
213054DS	220-240V	40W	0.9	4000K	4000lm	120°	50000h	1265*130*90	2.25
213055DS	220-240V	40W	0.9	5000K	4000lm	120°	50000h	1265*130*90	2.25
213056DS	220-240V	40W	0.9	6500K	4000lm	120°	50000h	1265*130*90	2.25

Part No.	Model No.	VEET Status	IPART Status
213034DS 213035DS 213036DS	ECT8BH5F-DS-2L60 20W	Pending	Pending
213054DS 213055DS 213056DS	ECT8BH5F-DS-2L120 40W	Pending	Pending

[1] Operating Frequency=50/60Hz;

[2] Multi-power description: 20W: 10/14/20W; 40W: 10/14/20/24/26/30/36/40W;

[3] Operating Temperature:-20 C~+45 C