



- Wattage switchable, dimmable LED batten with sensor and emergency option.



*Bi-level power switch on driver

FEATURES

- Built-in high efficiency SMD chips
- Powder coated steel base
- Highly transparent opal polycarbonate diffuser
- Variable wattage switchable
- Large 6mm terminal block for easy installation
- Quick install modular design
- Microwave sensor option available. Made to order and MOQ applies.
- Emergency option available, see page 73
- Fitting colour: White

INCLUDES

- LED Batten
- Multi-wattage switchable, 0-10V dimming LED driver
- Mounting accessories

INSTALLATION OPTIONS

- Surface mounted
- Suspended(suspension kit is required)

APPLICATIONS

- Offices
- Garages
- Stations
- Industrial

WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	Ra	DISTRIBUTION		DIMENSIONS(mm)

Part No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Size(L*W*H)mm	Net Weight (kg)
212013D	220-240V	20W	0.9	4000K	2000lm	120°	50000h	600*80*65	1.27
212014D	220-240V	40W	0.9	4000K	4000lm	120°	50000h	1200*80*65	1.92

Part No.	Model No.	VEET Status	IPART Status
212013D	YKT8BG2-D-2L60 20W	Pending	Pending
212014D	YKT8BG2-D-2L120 40W	Pending	Pending

[1] Operating Frequency=50/60Hz;
 [2] Multi-power description: 20W: 9/12/17W; 40W: 12/15/22/26/29/32W;
 [3] Operating Temperature:-20 °C~+50 °C
 [4] 5000K/6500K option available on request (MOQ applies)

Specifications are for reference only and may be changed without prior notification.

