



- Integrated weatherproof batten.



### FEATURES

- High efficiency SMD chips
- Constant current driver
- Large 6mm terminal block for easy installation
- High impact polycarbonate body and diffuser
- Stainless steel clips and screws
- IP65 weatherproof and IK08 vandal-proof
- Fitting colour: Grey

### INCLUDES

- IP65 batten with LED driver
- Stainless steel clips and screws
- Suspension bracket and cable gland

### INSTALLATION OPTIONS

- Surface mounted
- Suspended (Suspension kit is required)
- Side and top cable entry options

### APPLICATIONS

- Warehouses
- Car parks
- Stations
- Food preparation areas

### WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)	IK RATING
						 IK08 1.7kg at 300mm

Part No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Size(L*W*H)mm	Net Weight (kg)
213024	220-240V	10W	0.9	4000K	1000lm	120°	50000h	662*89*90	1.02
213034	220-240V	20W	0.9	4000K	2000lm	120°	50000h	662*130*90	1.26
213044	220-240V	20W	0.9	4000K	2000lm	120°	50000h	1265*89*90	1.71
213054	220-240V	40W	0.9	4000K	4000lm	120°	50000h	1265*130*90	2.12
213026	220-240V	10W	0.9	6500K	1000lm	120°	50000h	662*89*90	1.02
213036	220-240V	20W	0.9	6500K	2000lm	120°	50000h	662*130*90	1.26
213046	220-240V	20W	0.9	6500K	2000lm	120°	50000h	1265*89*90	1.71
213056	220-240V	40W	0.9	6500K	4000lm	120°	50000h	1265*130*90	2.12

Part No.	Model No.	VEET Status	IPART Status
213024 213026	ECT8BH4F-1L60 10W	Approved No.: 5464	Approved No.: 24143S20-HH8FADH
213034 213036	ECT8BH4F-2L60 20W	Approved No.: 5464	Approved No.: 24143S20-HH8FADH
213044 213046	ECT8BH4F-1L120 20W	Approved No.: 5464	Approved No.: 24143S20-HH8FADH
213054 213056	ECT8BH4F-2L120 40W	Approved No.: 5464	Approved No.: 24143S20-HH8FADH

[1] Operating Frequency=50/60Hz;

[2] Operating Temperature:-20 °C~+45 °C

Specifications are for reference only and may be changed without prior notification.

